

Mandrel built

Air hose

LIGHT DUTY AIR HOSE

- TUBE** : Air , water & oil mist resistant , smooth black SBR /NBR.
- REINFORCEMENT** : High tensile synthetic.
- COVER** : Abrasion, weather & ozone resistant smooth, black SBR /EPDM.
- APPLICATION** : Light duty compressed air services ; pneumatic machines & tools.
- TEMPERATURE** : -30° C ~ +85° C (22° F ~ 185° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1/2	12.7	23	10	150	30	600	60
5/8	16.0	26	10	150	30	600	60
3/4	19.0	29	10	150	30	600	60
1	25.4	37	10	150	30	600	60
1 1/4	31.8	46	10	150	30	600	60
1 1/2	38.1	52	10	150	30	600	60
2	51	65	10	150	30	600	60
2 1/2	63	78	10	150	30	600	60
3	76	92	10	150	30	600	60
3 1/2	90	106	10	150	30	600	40
4	102	118	10	150	30	600	40
5	127	147	10	150	30	600	40
6	152	172	10	150	30	600	40

MEDIUM DUTY AIR HOSE

- TUBE** : Air , water & oil mist resistant , smooth black SBR /NBR
- REINFORCEMENT** : High tensile synthetic
- COVER** : Abrasion, weather & ozone resistant smooth, black SBR /EPDM
- APPLICATION** : Use in construction & mining industries for pneumatic rock drills
- TEMPERATURE** : -30° C ~ +85° C (22° F ~ 185° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1/2	12.7	24	20	300	60	900	60
5/8	16.0	27	20	300	60	900	60
3/4	19.0	31	20	300	60	900	60
1	25.4	39	20	300	60	900	60
1 1/4	31.8	48	20	300	60	900	60
1 1/2	38.1	54	20	300	60	900	60
2	51	66	20	300	60	900	60
2 1/2	63	80	20	300	60	900	60
3	76	94	20	300	60	900	60
3 1/2	90	108	20	300	60	900	40
4	102	120	20	300	60	900	40
5	127	150	20	300	60	900	40
6	152	176	20	300	60	900	40