

Mandrel built

Steam hose

TEXTILE STEAM HOSE

- TUBE** : Seamless steam resistant black EPDM .
- REINFORCEMENT** : High tensile synthetic cord .
- COVER** : Steam, weather & ozone resistant, smooth, Black EPDM .
- APPLICATION** : Saturated steam
- TEMPERATURE** : -30° C ~ +165° C (-22° F ~ +330° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1/2	12.7	24	10	150	30	450	60
5/8	16.0	28	10	150	30	450	60
3/4	19.0	31	10	150	30	450	60
1	25.4	38	10	150	30	450	60
1 1/4	31.8	46	10	150	30	450	60
1 1/2	38.1	52	10	150	30	450	60
2	51	67	10	150	30	450	60

STEEL STEAM HOSE

- TUBE** : Seamless steam resistant black EPDM .
- REINFORCEMENT** : High tensile synthetic cord .
- COVER** : Steam, weather & ozone resistant, smooth, Red EPDM .
- APPLICATION** : Saturated steam
- TEMPERATURE** : -30° C ~ +208° C (-22° F ~ +400° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	ft
1/2	12.7	25	17	225	45	675	60
5/8	16.0	29	17	225	45	675	60
3/4	19.0	33	17	225	45	675	60
1	25.4	40	17	225	45	675	60
1 1/4	31.8	48	17	225	45	675	60
1 1/2	38.1	55	17	225	45	675	60
2	51	68	17	225	45	675	60
2 1/2	63	80	17	225	45	675	40
3	76	94	17	225	45	675	40
4	102	123	17	225	45	675	40