

Mandrel built

# Water hose

## MEDIUM PRESSURE WATER DELIVERY HOSE

- TUBE** : Air, water & oil mist resistant, smooth black SBR / NBR
- REINFORCEMENT** : High tensile synthetic cord with wire helix
- COVER** : Abrasion, weather & ozone resistant corrugated, black SBR / EPDM
- APPLICATION** : Used in construction industries & agriculture
- TEMPERATURE** : -30° C ~ +85° C ( -22° F ~ 185° F )



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1/2	12.7	20	10	150	30	450	60
5/8	16.0	24	10	150	30	450	60
3/4	19.0	28	10	150	30	450	60
1	25.4	34	10	150	30	450	60
1 1/4	31.8	41	10	150	30	450	60
1 1/2	38.1	48	10	150	30	450	60
2	51	62	10	150	30	450	60
2 1/2	63	74	10	150	30	450	60
3	76	88	10	150	30	450	40
4	102	116	10	150	30	450	40
5	127	142	10	150	30	450	40
6	152	168	10	150	30	450	40
8	203	221	10	150	30	450	12
10	254	272	10	150	30	450	12

## HIGH PRESSURE WATER DELIVERY HOSE

- TUBE** : Air, water & oil mist resistant, smooth black SBR / NBR
- REINFORCEMENT** : High tensile synthetic cord with wire helix
- COVER** : Abrasion, weather & ozone resistant corrugated, black SBR / EPDM
- APPLICATION** : Used in construction industries & agriculture for high pressure services
- TEMPERATURE** : -30° C ~ +85° C ( -22° F ~ 185° F )



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
2	51	63	17	255	51	765	60
3	76	90	17	255	51	765	60
4	102	117	17	255	51	765	40
5	127	144	17	255	51	765	40
6	152	170	17	255	51	765	30
8	203	222	17	255	51	765	12
10	254	274	17	255	51	765	12

Mandrel built

# Water hose

## MEDIUM PRESSURE WATER SUCTION & DELIVERY HOSE

- TUBE** : Air, water & oil mist resistant, smooth black SBR / NBR
- REINFORCEMENT** : High tensile synthetic cord with wire helix
- COVER** : Abrasion, weather & ozone resistant corrugated, black SBR / EPDM
- APPLICATION** : Used in construction industries & agriculture
- TEMPERATURE** : -30° C ~ +85° C ( -22° F ~ 185° F )



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
3/4	19	28	10	150	30	450	60
1	25.4	34	10	150	30	450	60
1 1/4	31.8	42	10	150	30	450	60
1 1/2	38.1	48	10	150	30	450	60
2	51	62	10	150	30	450	60
2 1/2	63	74	10	150	30	450	60
3	76	88	10	150	30	450	60
4	102	116	10	150	30	450	40
5	127	143	10	150	30	450	40
6	152	168	10	150	30	450	40
8	203	227	10	150	30	450	12
10	254	282	10	150	30	450	12
12	305	337	10	150	30	450	12

## HIGH PRESSURE WATER SUCTION & DELIVERY HOSE

- TUBE** : Air, water & oil mist resistant, smooth black SBR / NBR
- REINFORCEMENT** : High tensile synthetic cord with wire helix
- COVER** : Abrasion, weather & ozone resistant corrugated, black SBR / EPDM
- APPLICATION** : Used in construction industries & agriculture for high pressure services
- TEMPERATURE** : -30° C ~ +85° C ( -22° F ~ 185° F )



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
2	51	62	17	250	51	750	60
2 1/2	63	75	17	250	51	750	60
3	76	89	17	250	51	750	60
4	102	118	17	250	51	750	40
5	127	144	17	250	51	750	40
6	152	169	17	250	51	750	40
8	203	228	17	250	51	750	12
10	254	284	17	250	51	750	12
12	305	339	17	250	51	750	12

Mandrel built

# Water hose

## FLEXIBLE CORRUGATED WATER SUCTION & DELIVERY HOSE

- TUBE** : Air, water & oil mist resistant, smooth black SBR / NBR
- REINFORCEMENT** : High tensile synthetic cord with wire helix
- COVER** : Abrasion, weather & ozone resistant corrugated, black SBR / EPDM
- APPLICATION** : Used in construction industries & agriculture
- TEMPERATURE** : -30° C ~ +85° C ( -22° F ~ 185° F )



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1	25.4	34	10	150	30	450	60
1 1/4	31.8	42	10	150	30	450	60
1 1/2	38.1	48	10	150	30	450	60
2	51	62	10	150	30	450	60
2 1/2	63	74	10	150	30	450	60
3	76	88	10	150	30	450	60
4	102	116	10	150	30	450	40
5	127	142	10	150	30	450	40
6	152	168	10	150	30	450	40
8	203	223	10	150	30	450	12
10	254	280	10	150	30	450	12
12	305	333	10	150	30	450	12