


Hydraulic hose

4 SP DIN EN 856


- TUBE:** Inner tube in high quality synthetic rubber compounds
REINFORCEMENT: For high tensile steel wire spiral layers
COVER: Abrasion & weather resistant synthetic rubber
TEMPERATURE: -40°C ~ 100°C (+125°C for Max)



DN	ID		OD	WP		TP	BP	BEND RADIUS	WEIGHT
	mm	inch		mm	mm				
10	3/8	9.5	21.4	445	6450	890	1780	180	0.78
12	1/2	12.7	24.6	415	6000	830	1660	230	0.93
16	5/8	15.9	28.2	350	5000	700	1400	250	1.17
19	3/4	19.0	32.2	350	5000	700	1400	300	1.48
25	1	25.4	39.7	280	4000	560	1120	340	2.02
31	1 1/4	31.8	50.8	210	3000	420	840	460	3.05
38	1 1/2	38.1	57.2	185	2650	370	740	560	3.52
51	2	50.8	69.8	165	2360	330	660	660	5.20

4 SH DIN EN 856

- TUBE:** Inner tube in high quality synthetic rubber compounds
REINFORCEMENT: For high tensile steel wire spiral layers
COVER: Abrasion & weather resistant synthetic rubber
TEMPERATURE: -40°C ~ 100°C (+125°C for Max)



DN	ID		OD	WP		TP	BP	BEND RADIUS	WEIGHT
	mm	inch		mm	mm				
19	3/4	19.0	32.2	420	6095	840	1680	280	1.53
25	1	25.4	38.7	380	5515	760	1520	340	2.06
31	1 1/4	31.8	45.5	345	5000	690	1380	460	2.46
38	1 1/2	38.1	53.5	290	4200	580	1160	560	3.35
51	2	50.8	68.1	250	3625	500	1000	700	4.55