

Extrude

Welding hose

ACTYLENE & OXYGEN HOSE

- TUBE** : High ignition temperature synthetic rubber
REINFORCEMENT : High tensile, synthetic textile & filament yarn
COVER : Excellent ozone & weather resistant synthetic rubber,
 14 Lines, smooth, Red : actylene Blue : oxygen
APPLICATION : For use with welding & allied process in workshop, shipyards,
 construction sites and manufacturing industries .
TEMPERATURE : -20° C ~ +80° C



ID		OD	WP	BP	L
inch	mm	mm	bar	bar	m
1/4	6.3	14.5	20	60	100
5/16	8.0	16.5	20	60	100
3/8	9.5	18.5	20	60	100

TWINE WELDING HOSE

- TUBE** : High ignition temperature synthetic rubber
REINFORCEMENT : High tensile, synthetic textile & filament yarn
COVER : Excellent ozone & weather resistant synthetic rubber,
 smooth, Red : actylene Blue : oxygen
APPLICATION : For use with welding & allied process in workshop, shipyards,
 construction sites and manufacturing industries .
TEMPERATURE : -20° C ~ +80° C



ID		OD	WP	BP	L
inch	mm	mm	bar	bar	m
3/16+3/16	5.0+5.0	12.0+12.0	20	60	100
1/4+1/4	6.3+6.3	13.3+13.3	20	60	100
1/4+5/16	6.3+8.0	13.3+15.0	20	60	100
1/4+3/8	6.3+9.5	13.3+16.0	20	60	100
5/16+5/16	8.0+8.0	15.0+15.0	20	60	100
5/16+3/8	8.0+9.5	15.0+16.0	20	60	100
3/8+3/8	9.5+9.5	16.0+16.0	20	60	100
3/8+3/8	10.0+10.0	17.0+17.0	20	60	100

Extrude

Welding hose

L.P.G HOSE

- TUBE** : High ignition temperature synthetic rubber
- REINFORCEMENT** : High tensile, synthetic textile & filament yarn
- COVER** : Excellent ozone & weather resistant synthetic rubber, smooth surface , Orange : LPG
- APPLICATION** : For use with welding & allied process in workshop, shipyards, construction sites and manufacturing industries .
- TEMPERATURE** : -20° C ~ +80° C



ID		OD	WP	BP	L
inch	mm	mm	bar	bar	m
3/16	5.0	12.0	20	60	100
1/4	6.3	13.3	20	60	100
5/16	8.0	15.0	20	60	100
3/8	9.5	17.0	20	60	100

TWINE L.P.G HOSE

- TUBE** : High ignition temperature synthetic rubber
- REINFORCEMENT** : High tensile, synthetic textile & filament yarn
- COVER** : Excellent ozone & weather resistant synthetic rubber, smooth surface , Orange : LPG Blue : oxygen
- APPLICATION** : For use with welding & allied process in workshop, shipyards, construction sites and manufacturing industries .
- TEMPERATURE** : -20° C ~ +80° C



ID		OD	WP	BP	L
inch	mm	mm	bar	bar	m
3/16+3/16	5.0+5.0	12.0+12.0	20	60	100
1/4+1/4	6.3+6.3	13.3+13.3	20	60	100
5/16+5/16	8.0+8.0	15.0+15.0	20	60	100
3/8+3/8	9.5+9.5	17.0+17.0	20	60	100