

Mandrel built

Abrasion hose

CEMENT DELIVERY HOSE

- TUBE** : High abrasion resistant conductive black NR
- REINFORCEMENT** : High tensile synthetic cord with antistatic copper wire
- COVER** : Weather, ozone resistant, abrasion resistant, black EPDM
- APPLICATION** : Used for delivery of dry powder, slurry & cement
- TEMPERATURE** : -30° C ~ +70° C (-22° F ~ +158° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1	25.4	37	10	150	30	450	60
1 1/4	31.8	44	10	150	30	450	60
1 1/2	38.1	52	10	150	30	450	60
2	51	65	10	150	30	450	60
2 1/2	63	78	10	150	30	450	60
3	76	93	10	150	30	450	60
4	102	122	10	150	30	450	40
5	127	149	10	150	30	450	30
6	152	174	10	150	30	450	30

CEMENT SUCTION & DELIVERY HOSE

- TUBE** : High abrasion resistant conductive black NR
- REINFORCEMENT** : High tensile synthetic cord with antistatic copper wire
- COVER** : Weather, ozone resistant, abrasion resistant, black EPDM
- APPLICATION** : Used for delivery of dry powder, slurry & cement
- TEMPERATURE** : -30° C ~ +70° C (-22° F ~ +158° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1	25.4	39	10	150	30	450	60
1 1/4	31.8	45	10	150	30	450	60
1 1/2	38.1	52	10	150	30	450	60
2	51	66	10	150	30	450	60
2 1/2	63	80	10	150	30	450	60
3	76	94	10	150	30	450	60
4	102	122	10	150	30	450	40
5	127	149	10	150	30	450	30
6	152	174	10	150	30	450	30

Mandrel built

Abrasion hose

HEAVY DUTY CEMENT DELIVERY HOSE

- TUBE** : High abrasion resistant conductive black NR
- REINFORCEMENT** : High tensile synthetic cord with antistatic copper wire
- COVER** : Weather, ozone resistant, abrasion resistant, black EPDM
- APPLICATION** : Used for delivery of dry powder, slurry & cement
- TEMPERATURE** : -30° C ~ +70° C (-22° F ~ +158° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1	25.4	40	20	300	60	900	60
1 1/4	31.8	48	20	300	60	900	60
1 1/2	38.1	56	20	300	60	900	60
2	51	71	20	300	60	900	60
2 1/2	63	86	20	300	60	900	60
3	76	98	20	300	60	900	40
4	102	130	20	300	60	900	40
5	127	156	20	300	60	900	30
6	152	182	20	300	60	900	30

HEAVY DUTY CEMENT SUCTION & DELIVERY HOSE

- TUBE** : High abrasion resistant conductive black NR
- REINFORCEMENT** : High tensile synthetic cord with antistatic copper wire
- COVER** : Weather, ozone resistant, abrasion resistant, black EPDM
- APPLICATION** : Used for suction & discharge of dry powder, slurry & cement
- TEMPERATURE** : -30° C ~ +70° C (-22° F ~ +158° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1	25.4	40	20	300	60	900	60
1 1/4	31.8	48	20	300	60	900	60
1 1/2	38.1	56	20	300	60	900	60
2	51	71	20	300	60	900	60
2 1/2	63	86	20	300	60	900	60
3	76	98	20	300	60	900	40
4	102	130	20	300	60	900	40
5	127	156	20	300	60	900	30
6	152	182	20	300	60	900	30

Mandrel built

Abrasion hose

SANDBLAST HOSE

- TUBE** : High abrasion resistant conductive black NR / BR
- REINFORCEMENT** : High tensile synthetic cord with antistatic copper wire
- COVER** : Weather, ozone resistant, abrasion resistant, black SBR / EPDM
- APPLICATION** : Used for sandblast & cleaning surfaces
- TEMPERATURE** : -30° C ~ +70° C (-22° F ~ +158° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1/2	12.7	28	12	180	60	900	60
3/4	19.0	34	12	180	60	900	60
1	25.4	42	12	180	60	900	60
1	25.4	48	12	180	60	900	60
1 1/4	31.8	48	12	180	60	900	60
1 1/4	31.8	54	12	180	60	900	60
1 1/2	38.1	58	12	180	60	900	60
1 1/2	38.1	60	12	180	60	900	60
2	51	71	12	180	60	900	60
2	51	73	12	180	60	900	60
2 1/2	63	86	12	180	60	900	40
3	76	98	12	180	60	900	40
4	102	126	12	180	60	900	40

PLASTER / GROUTING HOSE

- TUBE** : High abrasion resistant conductive black NR / BR
- REINFORCEMENT** : High tensile synthetic cord with antistatic copper wire
- COVER** : Weather, ozone resistant, abrasion resistant, black SBR / EPDM
- APPLICATION** : Used for plaster & grouting services
- TEMPERATURE** : -30° C ~ +70° C (-22° F ~ +158° F)



ID		OD	WP		BP		L
inch	mm	mm	bar	psi	bar	psi	mt
1/2	12.7	27	40	600	120	1800	60
3/4	19	33	40	600	120	1800	60
1	25.4	39	40	600	120	1800	60
1 1/4	31.8	46	40	600	120	1800	60
1 1/2	38.1	54	40	600	120	1800	60
2	51	68	40	600	120	1800	60
2 1/2	63	80	40	600	120	1800	40
3	76	94	40	600	120	1800	40
4	102	120	40	600	120	1800	40
5	127	145	40	600	120	1800	30
6	152	169	40	600	120	1800	30